

Kuhnke FIO MIX 04

EtherCAT®- Multifunktions-Busklemmen

This module series combines many different I/O signals to an intelligent module, saving the limited space in the control cabinet and reducing the variety of modules required in an EtherCAT® system. Under the system name FIO MIX complements the series of highly compact and multifunctional I/O modules the Kuhnke EtherCAT I/O family.

The Kuhnke FIO MIX 04 module provides besides 4 analogue inputs and 4 analogue outputs, each configurable for current and voltage, 2 encoder interfaces for signal collection of incremental (HTL/TTL) or absolute value position encoders with SSI or EnDAT interface. As an alternative 6 event counters can be configured as well. The configuration in CODESYS is done by plugable modules with corresponding slots. Each slot thereby represents one analogue channel or an encoder interface. This procedure bases on "EtherCAT Modular Device Profile".

Integrated functions:

- Functions selectable by using CODESYS V3 libraries
- Signal preprocessing on the module
- Customizing possible



Technical Data

Type	Kuhnke FIO Mix 04
Order no.	694 444 64
Counter / encoder	2 (configurable): RS422: 32 Bit, 20 Mio. Inc/s (5MHz) 5/24V SE: 32 Bit, 1,6 Mio. Inc/s (400kHz) SSI: 16 ... 32 Bit, 80 ... 1000 Kbit/s EnDat 2.1: 16 ... 40 Bit, 100 kHz ... 2 MHz alternative 6 event counter: 32 Bit, 1 kHz
Analogue inputs	4x 12 Bit (configurable): 0 ... 10 V, 0/4 ... 20 mA
Analogue outputs	4x 16 Bit (configurable): 0 ... 10 V, -10 ... +10 V, 0/4 ... 20 mA
Specialties	EtherCAT operation in Free RUN or DC-synchronous mode, analogue values scalable in physical or user-specific units
Power supply	24 VDC (-20% / +25%)
Fieldbus	EtherCAT® 100 Mbit/s LVDS: E-Bus
Mounting	35 mm DIN-Rail
Indication	LED, assigned to the clamping point locally
Shield connection	Directly at module
I/O connection	Spring-loaded plug with mechanical ejection
Ambience conditions	0 °C...+55 °C, IP 20, Interference immunity Zone B acc. EN 61131-2
Housing (W x H x D)	Aluminium, plastic, 25 x 120 x 90 mm
Certifications	CE, cULus

We reserve the rights of modification, omission, error with respect to the products. Illustrations similar. All rights reserved by the individual copyright holders. EtherCAT® is registered trademark and patented technology, licensed by Beckhoff Automation GmbH, Germany. Safety over EtherCAT® is registered trademark and patented technology, licensed by Beckhoff Automation GmbH, Germany. Microsoft®, Windows® and the Windows® Logo are registered trademarks of Microsoft Corporation in the USA and other countries. At www.plcopen.org you will find more information about PLCopen Organisation. CODESYS is a product of 3S-Smart Software Solutions GmbH. CiA® and CANopen® are registered community trademarks of CAN in Automation e.V. . PROFINET® is a registered trademark of PROFIBUS and PROFINET International (PI).